

INTERNAL DIMENSIONS (MM)											
Description of measurement	U Height	Internal	Height	Internal	Fan Tray	Internal Width			Internal Depth		
		H2	H2	2 Way Sever Fan Unit	4 Way Sever Fan Unit	W2	W3	W4	D2	D3	D4
		in u	in mm	2F	4F						
600 x 600											
009-000-001-18	18U	18U	800.1	Integral to frame. No loss of U space	Integral to frame. No loss of U space	597	45	465.1	597	540	25
009-000-001-24	24U	24U	1066.8			597	45	465.1	597	540	25
009-000-001-27	27U	27U	1200.15			597	45	465.1	597	540	25
009-000-001-33	32U	32U	1422.4			597	45	465.1	597	540	25
009-000-001-39	39U	39U	1733.55			597	45	465.1	597	540	25
009-000-001-42	42U	42U	1866.9			597	45	465.1	597	540	25
009-000-001-45	45U	45U	2000.25	597	45	465.1	597	540	25		
600 x 780											
009-000-009-28	18U	18U	800.1	Integral to frame. No loss of U space	Integral to frame. No loss of U space	597	45	465.1	777	720	25
009-000-009-34	24U	24U	1066.8			597	45	465.1	777	720	25
009-000-009-37	27U	27U	1200.15			597	45	465.1	777	720	25
009-000-009-32	32U	32U	1422.4			597	45	465.1	777	720	25
009-000-009-49	39U	39U	1733.55			597	45	465.1	777	720	25
009-000-009-52	42U	42U	1866.9			597	45	465.1	777	720	25
009-000-009-64	45U	45U	2000.25	597	45	465.1	777	720	25		
780 x 600											
009-000-002-19	18U	18U	800.1	Integral to frame. No loss of U space	Integral to frame. No loss of U space	697	45	465.1	597	540	25
009-000-002-25	24U	24U	1066.8			697	45	465.1	597	540	25
009-000-002-28	27U	27U	1200.15			697	45	465.1	597	540	25
009-000-002-32	32U	32U	1422.4			697	45	465.1	597	540	25
009-000-002-40	39U	39U	1733.55			697	45	465.1	597	540	25
009-000-002-43	42U	42U	1866.9			697	45	465.1	597	540	25
009-000-002-46	45U	45U	2000.25	697	45	465.1	597	540	25		
780 x 780											
009-000-003-19	18U	18U	800.1	Integral to frame. No loss of U space	Integral to frame. No loss of U space	697	45	465.1	777	720	25
009-000-003-25	24U	24U	1066.8			697	45	465.1	777	720	25
009-000-003-28	27U	27U	1200.15			697	45	465.1	777	720	25
009-000-003-32	32U	32U	1422.4			697	45	465.1	777	720	25
009-000-003-40	39U	39U	1733.55			697	45	465.1	777	720	25
009-000-003-43	42U	42U	1866.9			697	45	465.1	777	720	25
009-000-003-46	45U	45U	2000.25	697	45	465.1	777	720	25		
Description of measurement		Internal Height	Internal Height			Overall Internal Width. Not usable space	Width edge of profile to Edge of Rack i.e. the space you have down the side of rack for cable	Centre to centre of profiles	Internal depth Inside door to inside door. Not usable.	DEPTH Profile distance will move from max forward to max rear position. Not recommended as gives very little space for cables etc.	Depth of >> interior of front door to max forward position of profile

Door Dimensions, Profile Punching and Static Loading											
U Height	Door Dimensions		Profile Punching Pattern	Static LOADING of cabinet							
	DW	DH in mm	Z	Jacking Feet	Light duty	Medium	Heavy	Plinth			
600 x 600											
009-000-001-18	18U	502	818.1	Please reference diagram Z	Maximum Static Load 400Kg						
009-000-001-24	24U	502	1084.8								
009-000-001-27	27U	502	1218.2								
009-000-001-33	32U	502	1440.4								
009-000-001-39	39U	502	1751.6								
009-000-001-42	42U	502	1884.9								
009-000-001-45	45U	502	2018.3								
600 x 780											
009-000-009-28	18U	502	818.1	Please reference diagram Z	Maximum Static Load 400Kg						
009-000-009-34	24U	502	1084.8								
009-000-009-37	27U	502	1218.2								
009-000-009-32	32U	502	1440.4								
009-000-009-49	39U	502	1751.6								
009-000-009-52	42U	502	1884.9								
009-000-009-64	45U	502	2018.3								
780 x 600											
009-000-002-19	18U	682	818.1	Please reference diagram Z	Maximum Static Load 400Kg						
009-000-002-25	24U	682	1084.8								
009-000-002-28	27U	682	1218.2								
009-000-002-32	32U	682	1440.4								
009-000-002-40	39U	682	1751.6								
009-000-002-43	42U	682	1884.9								
009-000-002-46	45U	682	2018.3								
780 x 780											
009-000-003-19	18U	682	818.1	Please reference diagram Z	Maximum Static Load 400Kg						
009-000-003-25	24U	682	1084.8								
009-000-003-28	27U	682	1218.2								
009-000-003-32	32U	682	1440.4								
009-000-003-40	39U	682	1751.6								
009-000-003-43	42U	682	1884.9								
009-000-003-46	45U	682	2018.3								
Description of measurement	door width= 600mm. 500mm. 800 width = 700mm. 1040 depth = 940mm.	door height		Maximum load for Floor Standing Racks of this design. NB: If you have a requirement for a 1000Kg Static Load Cabinet please ask sales 01376 346600							

Please note that the Maximum Static Load is determined by the lowest factor example 1) 45U Sever cabinet on Plinth = 400Kg example 2) 45U server cabinet on Light Duty Castors = 249Kg.